24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com

Classic Plus 14 Specifications

| Cooling Capacity (95° at 60% RH) (Btu/Hr) | 13,200 |
|---|-----------------------|
| Electronic Features (Control Panel/Thermostat Control | Programmable |
| Air Flow (CFM, High/Low) Evaporator | 440/380 |
| Air Flow (CFM, High/Low) Condenser | 880/760 |
| Operating Conditions (Min-Max at 50% RH) | 70 -113 °F |
| Voltage | 115/ 1 Phase |
| Min-Max Voltage | 105-125v |
| Power Consumption (KW) | 1.3 |
| Current Consumption (AMPS) | 11.9 |
| Circuit Breaker Size (AMPS) | 15 |
| NEMA Plug Configuration | 5-15 |
| Power Cord (Gauge/Length) | 14 AWG (3 core) 10 ft |
| Dimensions W X D X H (IN) | 19 x 26 x 41 |
| Weight (Net Weight/Shipping Weight)(LBS) | 166/197 |
| Humidity Removed at 60% RH (GAL/HR) | .67 |
| Drain Tank Capacity | 5 gallons |
| Refrigerant | R-410A |
| Sound Level (dB(A), High/Low) w/Duct | 57/55 |
| Max. Duct Length (Cold Duct Hose/Hot Duct Hose) | 30 ft/ 60 ft |
| | |



Plug Type 5-15P

