24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com PORTABLE AC
PORTABLE HEATERS
DEHUMIDIFIERS
AIR SCRUBBERS

Climate Pro K12 Specifications

Cooling Capacity (95° at 60% RH) (Btu/Hr)	12,000
Electronic Features (Control Panel/Thermostat Con	trol) Programmable
Air Flow (CFM, High/Low) Evaporator	410/330
Air Flow (CFM, High/Low) Condenser	760/640
Operating Conditions (Min-Max at 50% RH)	65-95°F
Voltage	115/1
Min-Max Voltage	104-127
Power Consumption (KW)	1.2
Current Consumption (AMPS)	10.3
Circuit Breaker Size (AMPS)	15
NEMA Plug Configuration	5-15
Power Cord (Gauge/Length)	14 AWG (3 core)/10 ft
Dimensions W X D X H (IN)	22 X 27 X 47
Weight (Net Weight/Shipping Weight)(LBS)	166/208
Humidity Removed at 60% RH (GAL/HR)	0.58
Drain Tank Capacity	5 gallons
Refrigerant	R-410A
Sound Level (dB(A), High/Low) w/Duct	59/53
Max. Duct Length (Cold Duct Hose/Hot Duct Hose)	30 ft/60 ft



Plug Type 5-15P

