24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com PORTABLE AC
PORTABLE HEATERS
DEHUMIDIFIERS
AIR SCRUBBERS

Climate Pro K18 Specifications

Cooling Capacity (95° at 60% RH) (Btu/Hr)	16,800
Electronic Features (Control Panel/Thermostat Control	Programmable
Air Flow (CFM, High/Low) Evaporator	540/440
Air Flow (CFM, High/Low) Condenser	770/630
Operating Conditions (Min-Max)(at 50%RH)	65-95°F
Voltage	115/1
Min-Max Voltage	104-127
Power Consumption (KW)	1.7
Current Consumption (AMPS)	14.5
Circuit Breaker Size (AMPS)	20
NEMA Plug Configuration	5-20
Power Cord (Gauge/Length)	12 AWG (3 core)/10 ft
Dimensions W X D X H (IN)	22 X 27 X 47
Weight (Net Weight/Shipping Weight)(LBS)	172/209
Humidity Removed at 60% RH (GAL/HR)	0.96
Drain Tank Capacity	5 gallons
Refrigerant	R-410A
Sound Level (dB(A), High/Low) w/Duct	61/59
Max. Duct Length (Cold Duct Hose/Hot Duct Hose)	25 ft/60 ft



Plug Type 5-20P

