24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com PORTABLE AC
PORTABLE HEATERS
DEHUMIDIFIERS
AIR SCRUBBERS

Climate Pro X14 Specifications

Cooling Capacity (95° at 60% RH) (Btu/Hr)	13,200
Electronic Features (Control Panel/Thermostat Control	Programmable
Air Flow (CFM, High/Low) Evaporator	440/385
Air Flow (CFM, High/Low) Condenser	830/720
Operating Conditions (Min-Max at 50% RH)	70 -113 °F
Voltage	115/1 Phase
Min-Max Voltage	104-127v
Power Consumption (KW)	1.3
Current Consumption (AMPS)	11.5
Circuit Breaker Size (AMPS)	15
NEMA Plug Configuration	5-15
Power Cord (Gauge/Length)	14 AWG (3 core) 10 ft
Dimensions W X D X H (IN)	22 x 29 x 48
Weight (Net Weight/Shipping Weight)(LBS)	165/205
Humidity Removed at 60% RH (GAL/HR)	.67
Drain Tank Capacity	5 gallons
Refrigerant	R-410A
Sound Level (dB(A), High/Low) w/Duct	57/55
Max. Duct Length (Cold Duct Hose/Hot Duct Hose)	30 ft/ 60 ft



Plug Type 5-15P

