

24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com

PORTABLE AC PORTABLE HEATERS DEHUMIDIFIERS AIR SCRUBBERS

Climate Pro X18 Specifications

Cooling Capacity (95° at 60% RH) (Btu/Hr)		16,800
Electronic Features (Control Panel/Thermosta	t Control	Programmable
Air Flow (CFM, High/Low) Evaporator		565/475
Air Flow (CFM, High/Low) Condenser		890/760
Operating Conditions (Min-Max)(at 50%RH)		70-113°F
Voltage		115/1
Min-Max Voltage		104-127
Power Consumption (KW)		1.7
Current Consumption (AMPS)		15.5
Circuit Breaker Size (AMPS)		20
NEMA Plug Configuration		5-20
Power Cord (Gauge/Length)		12 AWG (3 core)/10 ft
Dimensions W X D X H (IN)		22 X 29 X 51
Weight (Net Weight/Shipping Weight)(LBS)		195/237
Humidity Removed at 60% RH (GAL/HR)		0.96
Drain Tank Capacity		5 gallons
Refrigerant		R-410A
Sound Level (dB(A), High/Low) w/Duct		64/62
Max. Duct Length (Cold Duct Hose/Hot Duct Hose)		30 ft/60 ft

Plug Type 5-20P



