24/7 Emergency On-Call 833-224-7368 GoAirSolutions.com PORTABLE AC
PORTABLE HEATERS
DEHUMIDIFIERS
AIR SCRUBBERS

Office Pro 60 Specifications

| Cooling Capacity (95° at 60% RH) (Btu/Hr) | | 60,000 |
|---|---|---------------------|
| Electronic Features (Control Panel/Thermostat Control | | Programmable |
| Air Flow (CFM, High/Low) Evaporator | | 630/545 |
| Air Flow (CFM, High/Low) Condenser | | 870/760 |
| Operating Conditions (Min-Max at 50% RH) | | 65-105°F |
| Voltage | | 208-230v/ 1 Phase |
| Min-Max Voltage | | 198-250v |
| Power Consumption (KW) | | 6.6 |
| Current Consumption (AMPS) | | 29 |
| Circuit Breaker Size (AMPS) | | 50 |
| NEMA Plug Configuration | | 6-50 |
| Power Cord (Gauge/Length) | | 6 AWG (3 core) 6 ft |
| Dimensions W X D X H (IN) | | 30 x 52 x 64 |
| Weight (Net Weight/Shipping Weight)(LBS) | | 623/732 |
| Humidity Removed at 60% RH (GAL/HR) | | 3.04 |
| Drain Tank Capacity | | Auto Pump Included |
| Refrigerant | | R-410A |
| Sound Level (dB(A), High/Low) w/Duct | | 69/67 |
| Max. Duct Length (Cold Duct Hose/Hot Duct Hose) | | 40 ft/100 ft |
| 5 . | - | |



Plug Type 6-50P

